

FILETTATURA ESTERNA SCOSTAMENTO A_0 / EXTERNAL THREAD DEVIATION A_0

PASSO / PITCH mm	SCOSTAMENTO A_0 DELLA POSIZIONE DELLA TOLLERANZA / DEVIATION A_0 OF POSITION TOLERANCE					
	c	d	e	f	g	h
0.2			-45	-32	-17	0
0.25			-45	-33	-18	0
0.3			-46	-33	-18	0
0.35			-46	-34	-19	0
0.4	(-120)	(-72)	-48	-34	-19	0
0.45	(-120)	(-73)	-48	-35	-20	0
0.5	(-122)	(-74)	-50	-36	-20	0
0.6	(-124)	(-76)	-53	-36	-21	0
0.7	(-125)	(-78)	-56	-38	-22	0
0.75	(-126)	(-79)	-56	-38	-22	0
0.81	(-127)	(-80)	-60	-38	-24	0
1	-130	-85	-60	-40	-26	0
1.25	-135	-90	-63	-42	-28	0
1.5	-140	-95	-67	-45	-32	0
1.75	-145	-100	-71	-48	-34	0
2	-150	-105	-71	-52	-38	0
2.5	-160	-110	-80	-58	-42	0
3	-170	-115	-85	-63	-48	0
3.5	-180	-125	-90	-70	-53	0
4	-190	-130	-95	-75	-60	0
4.5	-200	-135	-100	-80	-63	0
5	-212	-140	-106	-85	-71	0
5.5	-224	-150	-112	-90	-75	0
6	-235	-155	-118	-95	-80	0
8	-265	-180	-140	-118	-100	0